



2 апреля 2019 г.

Артикул:

V1-R0-00435-10000-2001230+V1-R0-00435-10001-2000000

Наименование:

Светильник светодиодный VARTON FLEX 50 12Вт 3000К 50x73мм

ТАБЛИЦА КОЭФФИЦИЕНТОВ ИСПОЛЬЗОВАНИЯ										
КОЭФФИЦИЕНТЫ ОТРАЖЕНИЯ										
ПОТОЛОК	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
СТЕНЫ	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
ПОЛ	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ИНДЕКС КОМНАТЫ	КОЭФФИЦИЕНТЫ ИСПОЛЬЗОВАНИЯ (В ПРОЦЕНТАХ) $k(RI) \times RCR = 5$									
k=0.60	85	78	74	84	78	74	84	78	74	70
0.80	93	86	82	92	86	82	91	86	82	78
1.00	98	92	88	97	91	88	95	91	87	83
1.25	102	96	93	101	96	92	99	95	92	87
1.50	105	100	96	104	99	96	101	98	95	90
2.00	108	103	100	106	102	99	104	100	98	92
2.50	110	106	102	108	104	102	105	102	100	94
3.00	111	108	105	109	106	104	106	104	102	95
4.00	113	110	108	111	109	107	108	106	104	97
5.00	115	112	110	113	110	109	109	107	106	98
СОГЛАСНО DIN EN 13032-2 2004										
ТАБЛИЦА ОБЪЕДИНЕННОГО ПОКАЗАТЕЛЯ ДИСКОМФОРТА (UGR)										
КОЭФФИЦИЕНТЫ ОТРАЖЕНИЯ										
ПОТОЛОК	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
СТЕНЫ	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
ПОЛ	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
РАЗМЕРЫ ПОМЕЩЕНИЯ	ПОПЕРЕК ПРОДОЛЬНОЙ ОСИ					ВДОЛЬ ПРОДОЛЬНОЙ ОСИ				
x=2H / y=2H	17.3	18.2	17.5	18.4	18.6	17.6	18.5	17.8	18.7	18.9
3H	17.2	18.1	17.5	18.3	18.5	17.5	18.4	17.8	18.6	18.8
4H	17.2	18.0	17.5	18.2	18.5	17.5	18.3	17.8	18.5	18.8
6H	17.1	17.9	17.4	18.1	18.4	17.4	18.2	17.7	18.4	18.7
8H	17.1	17.8	17.4	18.1	18.3	17.3	18.1	17.7	18.4	18.6
12H	17.0	17.7	17.3	18.0	18.3	17.3	18.0	17.6	18.3	18.6
x=4H / y=2H	17.1	17.9	17.4	18.1	18.4	17.4	18.2	17.7	18.5	18.7
3H	17.1	17.8	17.4	18.1	18.4	17.4	18.1	17.7	18.4	18.7
4H	17.1	17.7	17.4	18.0	18.3	17.3	18.0	17.7	18.3	18.6
6H	17.0	17.6	17.4	17.9	18.2	17.2	17.8	17.6	18.2	18.5
8H	16.9	17.5	17.3	17.8	18.2	17.2	17.7	17.6	18.1	18.4
12H	16.9	17.4	17.3	17.7	18.1	17.1	17.6	17.6	18.0	18.4
x=8H / y=4H	17.0	17.5	17.3	17.8	18.2	17.2	17.8	17.6	18.1	18.5
6H	16.9	17.3	17.3	17.7	18.1	17.1	17.6	17.6	18.0	18.4
8H	16.8	17.2	17.2	17.6	18.0	17.1	17.5	17.5	17.9	18.3
12H	16.7	17.1	17.2	17.5	18.0	17.0	17.3	17.5	17.8	18.3
x=12H / y=4H	16.9	17.4	17.3	17.8	18.1	17.2	17.7	17.6	18.0	18.4
6H	16.8	17.2	17.2	17.6	18.0	17.1	17.5	17.5	17.9	18.3
8H	16.7	17.1	17.2	17.5	18.0	17.0	17.3	17.5	17.8	18.3
UGR СВЕТИЛЬНИКА										
0										

