



5 апреля 2019 г.

Артикул:

V1-R0-00435-10000-2001230+V1-R0-00435-10012-2000000

Наименование:

Светильник светодиодный VARTON FLEX 50 12Вт 3000К 50x73мм

ТАБЛИЦА КОЭФФИЦИЕНТОВ ИСПОЛЬЗОВАНИЯ										
КОЭФФИЦИЕНТЫ ОТРАЖЕНИЯ										
ПОТОЛОК	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
СТЕНЫ	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
ПОЛ	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ИНДЕКС КОМНАТЫ	КОЭФФИЦИЕНТЫ ИСПОЛЬЗОВАНИЯ (В ПРОЦЕНТАХ) $k(RI) \times RCR = 5$									
k=0.60	85	78	74	85	78	74	84	78	74	70
0.80	93	87	83	92	87	83	91	86	82	79
1.00	98	92	88	97	92	88	96	92	88	83
1.25	102	97	93	101	96	93	99	95	92	88
1.50	105	100	97	104	100	96	102	98	95	91
2.00	108	104	101	107	103	100	104	101	98	93
2.50	110	106	103	108	105	102	105	102	100	94
3.00	111	108	105	110	107	104	106	104	102	95
4.00	114	111	108	111	109	107	108	106	104	97
5.00	115	112	110	113	111	109	109	107	106	98
СОГЛАСНО DIN EN 13032-2 2004										
ТАБЛИЦА ОБЪЕДИНЕННОГО ПОКАЗАТЕЛЯ ДИСКОМФОРТА (UGR)										
КОЭФФИЦИЕНТЫ ОТРАЖЕНИЯ										
ПОТОЛОК	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
СТЕНЫ	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
ПОЛ	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
РАЗМЕРЫ ПОМЕЩЕНИЯ	ПОПЕРЕК ПРОДОЛЬНОЙ ОСИ					ВДОЛЬ ПРОДОЛЬНОЙ ОСИ				
x=2H / y=2H	15.8	16.8	16.1	17.0	17.1	16.4	17.3	16.6	17.5	17.7
3H	15.7	16.6	16.0	16.8	17.0	16.2	17.1	16.5	17.3	17.5
4H	15.6	16.4	15.9	16.7	16.9	16.1	17.0	16.4	17.2	17.4
6H	15.5	16.3	15.8	16.5	16.8	16.1	16.8	16.4	17.1	17.3
8H	15.5	16.2	15.8	16.5	16.7	16.0	16.8	16.3	17.0	17.3
12H	15.4	16.1	15.8	16.4	16.7	16.0	16.7	16.3	16.9	17.2
x=4H / y=2H	15.6	16.5	15.9	16.7	16.9	16.2	17.0	16.5	17.2	17.4
3H	15.5	16.2	15.8	16.5	16.7	16.0	16.7	16.3	17.0	17.3
4H	15.4	16.0	15.7	16.3	16.6	15.9	16.6	16.3	16.9	17.2
6H	15.3	15.9	15.7	16.2	16.5	15.8	16.4	16.2	16.7	17.1
8H	15.3	15.8	15.6	16.1	16.5	15.8	16.3	16.2	16.7	17.0
12H	15.2	15.7	15.6	16.1	16.4	15.7	16.2	16.1	16.6	17.0
x=8H / y=4H	15.3	15.8	15.6	16.1	16.5	15.8	16.3	16.2	16.7	17.0
6H	15.2	15.6	15.6	16.0	16.4	15.7	16.1	16.1	16.5	16.9
8H	15.1	15.5	15.5	15.9	16.3	15.6	16.0	16.1	16.4	16.9
12H	15.0	15.4	15.5	15.8	16.3	15.6	15.9	16.0	16.3	16.8
x=12H / y=4H	15.2	15.7	15.6	16.1	16.4	15.7	16.2	16.1	16.6	17.0
6H	15.1	15.5	15.5	15.9	16.3	15.6	16.0	16.1	16.4	16.9
8H	15.0	15.4	15.5	15.8	16.3	15.6	15.9	16.0	16.3	16.8
UGR СВЕТИЛЬНИКА										
0										

